

Approx. weight

Material	lb	kg
Carbon steel	228	104
Stainless steel 304 and 304L	230	104
Stainless steel 316 and 316L	233	106

Densities 7.85, 7.9 and 8.0 g/cm3.
Calculated from the dimensions as the standard gives them, with no allowance for tolerance.



Section



20 holes Ø1.38
Face view

Lap joint flange, ASME B16.5 Class 300

NPS 16 (DN 400)

Dimensions per ASME B16.5-2025, inches and millimetres as the standard's own tables give them.
Lap joint flange: no raised face; it seats on the stub end lap.
Reference drawing. The purchase order and ASME B16.5 govern. Check the latest edition.
Generated at rajendradatacenter.us/flanges/lap-joint/

Dimension	in	mm
O Outside diameter	25.50	648
tf Flange thickness	2.25	57.2
Y Length through hub	4.75	121
X Hub diameter at base	19.00	483
B Bore	16.19	411.2
r Corner radius of bore	0.50	13
W Bolt circle diameter	22.50	571.5
h Bolt holes, 20 off	1.38	34.9

20 stud bolts of 1-1/4 in; holes 1.38 in (34.9 mm)

RAJENDRA INDUSTRIAL CORPORATION
rajendradatacenter.us
Drawing RIC-B165-LJ300-16
Scale 1:8 on Letter
Units: inches (mm)
Date 2026-11-22
Quote: rajendradatacenter.us/rfq/
sales@rajendradatacenter.com
+91 74338 71355