

**Approx. weight**

| Material | lb | kg |
|---|---|---|
| Carbon steel | 345 | 156 |
| Stainless steel 304 and 304L | 347 | 157 |
| Stainless steel 316 and 316L | 351 | 159 |

Densities 7.85, 7.9 and 8.0 g/cm3.
Calculated from the dimensions as the standard gives them, with no allowance for tolerance.




Section




24 holes Ø1.38

Face view

# Lap joint flange, ASME B16.5 Class 300

NPS 20 (DN 500)

Dimensions per ASME B16.5-2025, inches and millimetres as the standard's own tables give them.
Lap joint flange: no raised face; it seats on the stub end lap.
Reference drawing. The purchase order and ASME B16.5 govern. Check the latest edition.
Generated at rajendradatacenter.us/flanges/lap-joint/

| Dimension | in | mm |
|---|---|---|
| O Outside diameter | 30.50 | 775 |
| tf Flange thickness | 2.50 | 63.5 |
| Y Length through hub | 5.50 | 140 |
| X Hub diameter at base | 23.12 | 587 |
| B Bore | 20.25 | 514.4 |
| r Corner radius of bore | 0.50 | 13 |
| W Bolt circle diameter | 27.00 | 685.8 |
| h Bolt holes, 24 off | 1.38 | 34.9 |

24 stud bolts of 1-1/4 in; holes 1.38 in (34.9 mm)

RAJENDRA INDUSTRIAL CORPORATION

rajendradatacenter.us
Drawing RIC-B165-LJ300-20
Scale 1:10 on Letter
Units: inches (mm)
Date 2026-11-22
Quote: rajendradatacenter.us/rfq/
sales@rajendradatacenter.com
+91 74338 71355