

Approx. weight

Material	lb	kg
Carbon steel	164	74.6
Stainless steel 304 and 304L	165	75.0
Stainless steel 316 and 316L	167	76.0

Densities 7.85, 7.9 and 8.0 g/cm3.
Calculated from the dimensions as the standard gives them, with no allowance for tolerance.



Section



16 holes Ø1.38

Face view

Lap joint flange, ASME B16.5 Class 600

NPS 10 (DN 250)

Dimensions per ASME B16.5-2025, inches and millimetres as the standard's own tables give them.
Lap joint flange: no raised face; it seats on the stub end lap.
Reference drawing. The purchase order and ASME B16.5 govern. Check the latest edition.
Generated at rajendradatacenter.us/flanges/high-pressure/

Dimension	in	mm
O Outside diameter	20.00	508
tf Flange thickness	2.50	63.5
Y Length through hub	4.38	111
X Hub diameter at base	13.50	343
B Bore	10.92	277.4
r Corner radius of bore	0.50	13
W Bolt circle diameter	17.00	431.8
h Bolt holes, 16 off	1.38	34.9

16 stud bolts of 1-1/4 in; holes 1.38 in (34.9 mm)

RAJENDRA INDUSTRIAL CORPORATION
rajendradatacenter.us
Drawing RIC-B165-LJ600-10
Scale 1:6 on Letter
Units: inches (mm)
Date 2026-11-22
Quote: rajendradatacenter.us/rfq/
sales@rajendradatacenter.com
+91 74338 71355