

Approx. weight

Material	lb	kg
Carbon steel	12.4	5.6
Stainless steel 304 and 304L	12.5	5.7
Stainless steel 316 and 316L	12.6	5.7

Densities 7.85, 7.9 and 8.0 g/cm3.
Calculated from the dimensions as the standard gives them, with no allowance for tolerance.



Section



8 holes Ø0.88
Face view

Slip-on flange, Class 150 RF, ASME B16.5 drilling

NPS 5 (DN 125)

ASME B16.5 slip-on flanges have a hub. This flange keeps the B16.5 outside diameter, drilling, raised face and slip-on bore without it.
Thickness shown is the B16.5 minimum; confirm the thickness for a flange without a hub in the order.
tf is measured without the 0.06 in (1.5 mm) raised face; the tf + f row is the same flange measured over the face.
Reference drawing. The purchase order governs.
Generated at rajendradatacenter.us/flanges/slip-on/

Dimension	in	mm
O Outside diameter	10.00	254
R Raised face diameter	7.31	185.7
f Raised face height	0.06	1.5
tf Thickness (min), without raised face	0.88	22.4
tf + f Thickness over the raised face	0.94	23.9
B Bore	5.66	143.8
W Bolt circle diameter	8.50	215.9
h Bolt holes, 8 off	0.88	22.2

8 stud bolts of 3/4 in; holes 0.88 in (22.2 mm)

RAJENDRA INDUSTRIAL CORPORATION
rajendradatacenter.us
Drawing RIC-B165-PL150-5
Scale 1:3 on Letter
Units: inches (mm)
Date 2026-11-22
Quote: rajendradatacenter.us/rfq/
sales@rajendradatacenter.com
+91 74338 71355