Approx. weight

Material	lb	kg
Carbon steel	484	219
Stainless steel 304 and 304L	487	221
Stainless steel 316 and 316L	493	224

Densities 7.85, 7.9 and 8.0 g/cm3.
Calculated from the dimensions as the standard gives them, with no allowance for tolerance.



Section



24 holes Ø1.88

Face view

Slip-on flange with hub, ASME B16.5 Class 400 RF

NPS 24 (DN 600)

Dimensions per ASME B16.5-2025, inches and millimetres as the standard's own tables give them.
tf and Y are the ASME B16.5 dimension, measured without the 0.25 in (6.4 mm) raised face; the tf + f and Y + f rows are the same flange measured over the face, which is what most catalogs print.
Reference drawing. The purchase order and ASME B16.5 govern. Check the latest edition.
Generated at rajendradatacenter.us/flanges/high-pressure/

Dimension	in	mm
O Outside diameter	36.00	914
R Raised face diameter	27.25	692.2
f Raised face height	0.25	6.4
tf Thickness (min), without raised face	3.00	76.2
tf + f Thickness over the raised face	3.25	82.6
Y Length through hub, without raised face	4.50	114
Y + f Length through hub, over the raised face	4.75	120.4
X Hub diameter at base	27.62	702
B Bore	24.25	616
W Bolt circle diameter	32.00	812.8
h Bolt holes, 24 off	1.88	47.6

24 stud bolts of 1-3/4 in; holes 1.88 in (47.6 mm)

RAJENDRA INDUSTRIAL CORPORATION
rajendradatacenter.us
Drawing RIC-B165-SO400-24
Scale 1:12 on Letter
Units: inches (mm)
Date 2026-11-22
Quote: rajendradatacenter.us/rfq/
sales@rajendradatacenter.com
+91 74338 71355