

**Approx. weight**

| Material | lb | kg |
|---|---|---|
| Carbon steel | 224 | 101 |
| Stainless steel 304 and 304L | 225 | 102 |
| Stainless steel 316 and 316L | 228 | 103 |

Densities 7.85, 7.9 and 8.0 g/cm3.
Calculated from the dimensions as the standard gives them, with no allowance for tolerance.




Section




16 holes Ø1.50

Face view

# Slip-on flange with hub, ASME B16.5 Class 900 RJ

NPS 10 (DN 250)

Dimensions per ASME B16.5-2025, inches and millimetres as the standard's own tables give them.
Ring joint facing to ASME B16.5 Table 5, ring and groove number R53. The raised portion stands E above the flange, the same as the depth of the groove, so the bottom of the groove is level with the flange face. Ring joint gasket dimensions are to ASME B16.20 (clause 6.11.1).
tf and Y are the ASME B16.5 dimension, measured without the raised portion; the tf + E and Y + E rows are the same flange measured over the facing.
Reference drawing. The purchase order and ASME B16.5 govern. Check the latest edition.
Generated at rajendradatacenter.us/flanges/ring-type-joint/

| Dimension | in | mm |
|---|---|---|
| O Outside diameter | 21.50 | 546 |
| K Diameter of the raised portion | 14.25 | 362 |
| E Depth of the groove, and the raised portion | 0.31 | 7.92 |
| P Pitch diameter of the groove | 12.75 | 323.85 |
| F Width of the groove | 0.47 | 11.91 |
| r Radius at the bottom of the groove | 0.03 | 0.8 |
| tf Thickness (min), without the raised portion | 2.75 | 69.8 |
| tf + E Thickness over the raised portion | 3.06 | 77.7 |
| Y Length through hub, without the raised portion | 4.25 | 108 |
| Y + E Length through hub, over the raised portion | 4.56 | 115.9 |
| X Hub diameter at base | 14.50 | 368 |
| B Bore | 10.88 | 276.4 |
| W Bolt circle diameter | 18.50 | 469.9 |
| h Bolt holes, 16 off | 1.50 | 38.1 |

16 stud bolts of 1-3/8 in; holes 1.50 in (38.1 mm)

RAJENDRA INDUSTRIAL CORPORATION

rajendradatacenter.us
Drawing RIC-B165-SO900RJ-10
Scale 1:8 on Letter
Units: inches (mm)
Date 2026-11-22
Quote: rajendradatacenter.us/rfq/
sales@rajendradatacenter.com
+91 74338 71355