Approx. weight

Material	lb	kg
Carbon steel	499	226
Stainless steel 304 and 304L	502	228
Stainless steel 316 and 316L	509	231

Densities 7.85, 7.9 and 8.0 g/cm3.
Calculated from the dimensions as the standard gives them, with no allowance for tolerance.



Section



24 holes Ø1.75

Face view

Threaded flange, ASME B16.5 Class 600 RF

NPS 20 (DN 500)

Dimensions per ASME B16.5-2025, inches and millimetres as the standard's own tables give them.
Thread: NPT 20 taper pipe thread to ASME B1.20.1, 8 threads per inch, counterbored at the back (clause 6.9.3). The thread profile is drawn for illustration.
tf and Y are the ASME B16.5 dimension, measured without the 0.25 in (6.4 mm) raised face; the tf + f and Y + f rows are the same flange measured over the face, which is what most catalogs print.
Reference drawing. The purchase order and ASME B16.5 govern. Check the latest edition.
Generated at rajendradatacenter.us/flanges/high-pressure/

Dimension	in	mm
O Outside diameter	32.00	813
R Raised face diameter	23.00	584.2
f Raised face height	0.25	6.4
tf Thickness (min), without raised face	3.50	88.9
tf + f Thickness over the raised face	3.75	95.3
Y Length through hub, without raised face	5.00	127
Y + f Length through hub, over the raised face	5.25	133.4
X Hub diameter at base	24.00	610
B Bore	20.00	508.0
T Thread length, from the raised face	3.25	83
Q Counterbore at the back	20.19	512.8
W Bolt circle diameter	28.50	723.9
h Bolt holes, 24 off	1.75	44.5

24 stud bolts of 1-5/8 in; holes 1.75 in (44.5 mm)

RAJENDRA INDUSTRIAL CORPORATION
rajendradatacenter.us
Drawing RIC-B165-TH600-20
Scale 1:10 on Letter
Units: inches (mm)
Date 2026-11-22
Quote: rajendradatacenter.us/rfq/
sales@rajendradatacenter.com
+91 74338 71355