Bore B and approx. weight by pipe schedule

Schedule	B, in (mm)	CS lb (kg)	SS lb (kg)
Sch 5S / Sch 5	2.245 (57.0)	34.5 (15.7)	35.2 (16.0)
Sch 10S / Sch 10	2.157 (54.8)	35.0 (15.9)	35.6 (16.2)
Sch 30	2.125 (54.0)	35.1 (15.9)	35.8 (16.2)
Sch 40S / STD / Sch 40	2.067 (52.5)	35.4 (16.1)	36.1 (16.4)
Sch 80S / XS / Sch 80	1.939 (49.3)	36.0 (16.3)	36.7 (16.6)
Sch 160	1.687 (42.8)	37.1 (16.8)	37.8 (17.1)
XXS	1.503 (38.2)	37.8 (17.1)	38.5 (17.5)

B = A - 2 x pipe wall (ASME B36.10M and B36.19M).
CS carbon steel, 7.85 g/cm3. SS stainless steel 316L, 8.0 g/cm3; 304L (7.9 g/cm3) weighs about 1% less.
Calculated from the dimensions as the standard gives them, with no allowance for tolerance.



Section



8 holes Ø1.12
Face view

Weld neck flange, ASME B16.5 Class 2500 RF

NPS 2 (DN 50)

Dimensions per ASME B16.5-2025, inches and millimetres as the standard's own tables give them.
tf and Y are the ASME B16.5 dimension, measured without the 0.25 in (6.4 mm) raised face; the tf + f and Y + f rows are the same flange measured over the face, which is what most catalogs print.
Bore B to suit the pipe schedule: see the table. Other walls to order.
Reference drawing. The purchase order and ASME B16.5 govern. Check the latest edition.
Generated at rajendradatacenter.us/flanges/high-pressure/

Dimension	in	mm
O Outside diameter	9.25	235
R Raised face diameter	3.62	91.9
f Raised face height	0.25	6.4
tf Thickness (min), without raised face	2.00	50.8
tf + f Thickness over the raised face	2.25	57.2
Y Length through hub, without raised face	5.00	127
Y + f Length through hub, over the raised face	5.25	133.4
X Hub diameter at base	3.75	95
A Hub diameter at weld end (pipe OD)	2.38	60.5
W Bolt circle diameter	6.75	171.4
h Bolt holes, 8 off	1.12	28.6

8 stud bolts of 1 in; holes 1.12 in (28.6 mm)

RAJENDRA INDUSTRIAL CORPORATION
rajendradatacenter.us
Drawing RIC-B165-WN2500-2
Scale 1:4 on Letter
Units: inches (mm)
Date 2026-11-22
Quote: rajendradatacenter.us/rfq/
sales@rajendradatacenter.com
+91 74338 71355